

HIGHLY EFFICIENT SOFT MOUNTED WASHER EXTRACTORS



FX 350	FX 450	FX 600
35KG	45KG	60KG
<i>77</i> LB	99LB	132LB



FEATURES

- Freestanding, high spin
- Patented Cascade Drum™
- Stainless steel drum and tub
- Xcontrol PlusTM Fully programmable
- 3rd water inlet, high inlets capacity
- 2x large drain valves (Ø 76 mm)
- Easy Soap[™] liquid soaps connection
- Large door opening for easy loading unloading
- Ergonomic height of door enables easy access with trolleys
- USB and RS485 plug (on the back panel)
- User Friendly control position regardless
- Bumper (front side protection)
- Soap hopper new sleek design

OPTIONS

- Stainless steel front
- Liquid soap pumps
- Recycle valve
- Steam heating version
- Air operated water inlets
- OPTILOAD™ weighing system
- Water sample tap
- Extra signalization (orange light & horn)
- Isolation for energy and noise reduction
- Forward tilting (n/a for FX350)
- Trace-Tech™ laundry management software

















LARGE DOOR OPENING



LOW WATER AND ENERGY CONSUMPTION

TYPE		FX350	FX450	FX600
INNER DRUM				
capacity	kg	35	45	60
volume	litres	350	450	600
diameter	mm	914	914	1035
DRUM SPEED				
wash	rpm	45	45	42
extraction	rpm	839	839	788
G-FACTOR		360	360	360
HEATING				
electricity	kW	24	36	54
steam	bar	3-8	3-8	3-8
hot water	°C	90	90	90
Sound pressure level	dB (A)	<75	<75	<75
Water valves connection	BSP	1"	1"	1"
Water pressure	kPa	100-800	100-800	100-800
Rec. water pressure	kPa	300-500	300-500	300-500
Water inlet	l/min	578	578	578
Drain valve	outer Ø mm	2x76	2×76	2x76
Flow amount with drain	l/min			
valve		210	210	210
Steam valve connection	BSP	3/4"	3/4"	3/4"
Steam pressure	kPa	300-800	300-800	300-800
DIMENSIONS				
Size H×W×D	mm	1925×1315×1270	1925x1315x1502	1925x1315x1502
Net weight	kg	1010	1350	1500
TRANSPORT DATA				
Packed H×W×D	mm	2125x1425x1470	2125×1425×1700	2125x1425x1700
Gross weight	kg	1170	1490	1640

